

# XR GRAINCARTS

## SPECIFICATIONS

	820XR		1020XR		1120XR		1322XR	
<b>Performance</b>								
Capacity (bushels)	850		1,000		1,100		1,300	
Unload Speed (bu/min)	500		500		500		620	
Minimum Horsepower	200		200		200		250	
<b>General</b>								
Auger Diameter	20"		20"		20"		20" with 22" Booster	
Flighting	1/2" Extended Life		1/2" Extended Life		1/2" Extended Life		1/2" Extended Life	
Discharge Travel	105°		105°		105°		105°	
<b>Undercarriage</b>								
	<b>Tires</b>	<b>Tracks</b>	<b>Tires</b>	<b>Tracks</b>	<b>Tires</b>	<b>Tracks</b>	<b>Tires</b>	<b>Tracks</b>
Standard Tire/Track Size*	30.5 x 32	103" x 36"	900/60R32	103" x 36"	IF900/60R32	103" x 36"	520/85R42	136" x 36"
Axle Spindle Diameter	3.75"	4.5"	4.5"	4.5"	4.5"	4.5"	3.75"	5.5"
Loaded Surface Ground Pressure (psi)	34	12	58	14	50	14	66	13
<b>Weight</b>								
Empty	12,000 lb	18,000 lb	12,300 lb	19,000 lb	12,400 lb	19,100 lb	21,200 lb	33,000 lb
Tongue - Empty	1,100 lb (Standard) 1,300 lb (Rear Axle Position)		1,100 lb (Standard) 1,300 lb (Rear Axle Position)		1,100 lb (Standard) 1,300 lb (Rear Axle Position)		4,100 lb	4,100 lb
Tongue - Full	4,200 lb (Standard) 5,800 lb (Rear Axle Position)		4,700 lb (Standard) 6,600 lb (Rear Axle Position)		5,000 lb (Standard) 7,100 lb (Rear Axle Position)		6,500 lb	6,500 lb
<b>Dimensions</b>								
Height Hitch	1' - 2'3"	1' - 2'3"	1' - 2'3"	1' - 2'3"	1' - 2'3"	1' - 2'3"	1' - 2'3"	1' - 2'3"
Axle to Tongue Length	16' 8"	16' 8"	16' 8"	16' 8"	16' 8"	16' 8"	20'	20'
Overall Length	31'	31'	31'	31'	31'	31'	33'	33'
Hopper Length	21' 2"	21' 2"	21' 2"	21' 2"	21' 2"	21' 2"	24'	24'
Auger Forward Reach	4' 9"	4' 9"	4' 9"	4' 9"	4' 9"	4' 9"	13' 6"	13' 6"
Auger Unload Height	18' 1"	18' 2"	18' 3"	18' 2"	18' 3"	18' 2"	n/a	n/a
Discharge Height	13' 7"	13' 8"	13' 9"	13' 8"	13' 9"	13' 8"	13' 9"	13' 9"
Auger Reach	10' 11"	10' 11"	10' 11"	10' 11"	10' 11"	10' 11"	9'	9'
Overall Width	11' 10"	11' 10"	11' 10"	11' 10"	13' 9"	13' 9"	14' 3"	14' 3"
Loading Side Height	10' 7"	10' 9"	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"	11' 2"
Transport Height	12' 1"	12' 3"	13' 0"	13' 0"	12' 11"	12' 10"	13'	12' 11"
Wheel Outside Width	13' 8"	13' 3"	14' 4"	13' 3"	14' 4"	13' 3"	11'10"-12'7"-13'4"	13' 10"

\*Multiple tire sizes available

## FEATURES

### Obstruction-Free Ladder

Provides safe and easy access to the tank for maintenance.

### Camera Kit and In-Cab Monitor

Provides total visibility around the cart with up to three cameras.

### Load Management

Ensures consistent loading with Digistar scale options including wi-fi, GPS, and moisture-sensor modules.

### Walking-Beam Tandem Tires (1322XR)

Traverse rough terrain with ease.

### Drive Options

Enables compatibility with either PTO or hydraulic auger drive systems.

For more information  
Call us at 1-866-4-BRANDT  
Email us at [agriculture@brandt.ca](mailto:agriculture@brandt.ca)  
Or visit us at [www.brandt.ca](http://www.brandt.ca)

**Brandt Agricultural Products**  
PO Box 317, 13th Avenue & Pinkie Road,  
Regina, SK, Canada  
S4P 3A1

