

TWISTER SPECIFICATIONS									
	12'	16'	20'	24'	28'	32'	36'	40'	
Hydraulic Requirements (Ports)	3 or 4	3 or 4	3 or 4	3 or 4	3 or 4	3 or 4	3 or 4	3 or 4	3 or 4
Hydraulic Requirements (PSI)	3000	3000	3000	3000	3000	3000	3000	3000	3000
Tire Specifications	320/70R15	320/70R15	440/55R18	440/55R18	440/55R20	440/55R20	440/55R20	440/55R20	440/55R20
Horsepower Requirement (hp/ft)	12-15	12-15	12-15	12-15	12-15	12-15	12-15	12-15	12-15
Hub/Spindle Assembly	8-Bolt	6-Bolt	6-Bolt-Wing/Main	6-Bolt-Wing 8-Bolt-Main	6-Bolt-Wing 8-Bolt-Main	6-Bolt-Wing 10-Bolt-Main	6-Bolt-Wing 10-Bolt-Main	6-Bolt-Wing 10-Bolt-Main	6-Bolt-Wing 10-Bolt-Main
Frame Sections	1	1	3	3	3	3	3	3	3
# of Coulter Blades	24	32	40	48	56	64	72	80	
Coulter Blade Spacing	12"	12"	12"	12"	12"	12"	12"	12"	12"
Effective Cut Spacing	6"	6"	6"	6"	6"	6"	6"	6"	6"
Gang Angle Adjust (deg)	0°-7°	0°-7°	0°-7°	0°-7°	0°-7°	0°-7°	0°-7°	0°-7°	0°-7°
Tine Spacing (2-Row)	6"	6"	6"	6"	6"	6"	6"	6"	6"
Tine Spacing (3-Row)	4"	4"	4"	4"	4"	4"	4"	4"	4"
Basket Options	Flat Bar or Round Bar	Flat Bar or Round Bar	Flat Bar or Round Bar	Flat Bar or Round Bar	Flat Bar or Round Bar	Flat Bar or Round Bar	Flat Bar or Round Bar	Flat Bar or Round Bar	Flat Bar or Round Bar
Machine Dimensions "A"	8'	11'		16'-4"	16'-4"	20'-4"	20'-4"	20'-8"	
Machine Dimensions "B"	9'-5"	10'-5"		10'-1"	11'-6"	11'-6"	12'-11"	14'-10"	
Machine Dimensions "C"	12"	16'		24'	28'	32'	36'	40'	
Machine Dimensions "D"	29'-3"	29'-3"		28'-2"	28'-2"	28'-2"	28'-2"	28'-2"	28'-2"
Machine Dimensions "E"	5'-6"	5'-11"		5'-6"	5'-6"	5'-6"	5'-6"	6'-6"	